

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: C2 562 - FLEXOTHINNER PE 20

Other means of identification:

UFI: 3V00-P0DN-8002-F88W

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Printing Relevant identified uses:

SU3 Industrial use, as such or in mixtures on industrial locations

SU9 Manufacture of fine chemicals

SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU24 Scientific research and development

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

ECP d.o.o. Brnčičeva 45 1231 Ljubljana - Slovenia

Phone: +386 1 562 05 84

office@ecp.eu www.ecp.si

1.4 Emergency telephone number: 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Flam. Liq. 2: Flammable liquids, Category 2, H225

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger





Hazard statements:

Flam. Liq. 2: H225 - Highly flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground and bond container and receiving equipment.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Substances that contribute to the classification

1-ethoxypropan-2-ol (CAS: 1569-02-4) **UFI:** 3V00-P0DN-8002-F88W

Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

2.3

Non-applicable

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixture:

Chemical description: Solvent/s

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS:	64-17-5	ethanol ⁽¹⁾ ATP CLP00				
EC: Index: REACH:	200-578-6 603-002-00-5 : 01-2119457610-43- XXXX	Regulation 1272/2008	Flam. Liq. 2: H225 - Danger	55 - <70 %		
CAS:	1569-02-4	1-ethoxypropan-2-ol	ATP CLP00			
EC: Index: REACH:	216-374-5 603-177-00-8 01-2119462792-32- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	35 - <45 %		
CAS:	78-93-3	Butanone ⁽³⁾	ATP CLP00			
EC: Index: REACH:	201-159-0 606-002-00-3 : 01-2119457290-43- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	<1 %		
CAS:	67-63-0 200-661-7 603-117-00-0 : 01-2119457558-25- XXXX	propan-2-ol(1)	ATP CLP00			
EC: Index: REACH:		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	<1 %		

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Date of compilation: 23/10/2024 Version: 1 Page 2/13

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽³⁾ Substance with a Union workplace exposure limit



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 5: FIREFIGHTING MEASURES (continued)

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Other information:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification				Occupational exposure limits			
Butanone					IOELV (8h)	200 ppm	600 mg/m ³
CAS: 78-93-3 EC: 201-159-0					IOELV (STEL)	300 ppm	900 mg/m ³

DNEL (Workers):

	Short exposure		Long exposure		
Identification		Systemic	Local	Systemic	Local
ethanol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64-17-5	Dermal	Not relevant	Not relevant	343 mg/kg	Not relevant
EC: 200-578-6	Inhalation	Not relevant	Not relevant	950 mg/m ³	Not relevant
1-ethoxypropan-2-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 1569-02-4	Dermal	Not relevant	Not relevant	74 mg/kg	Not relevant
EC: 216-374-5	Inhalation	Not relevant	Not relevant	106 mg/m ³	Not relevant
Butanone	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 78-93-3	Dermal	Not relevant	Not relevant	1161 mg/kg	Not relevant
EC: 201-159-0	Inhalation	Not relevant	Not relevant	600 mg/m ³	Not relevant
propan-2-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 67-63-0	Dermal	Not relevant	Not relevant	888 mg/kg	Not relevant
EC: 200-661-7	Inhalation	1000 mg/m ³	Not relevant	500 mg/m ³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
ethanol	Oral	Not relevant	Not relevant	87 mg/kg	Not relevant
CAS: 64-17-5	Dermal	Not relevant	Not relevant	206 mg/kg	Not relevant
EC: 200-578-6	Inhalation	Not relevant	Not relevant	114 mg/m³	Not relevant

Page 4/13

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
1-ethoxypropan-2-ol	Oral	Not relevant	Not relevant	14 mg/kg	Not relevant	
CAS: 1569-02-4	Dermal	Not relevant	Not relevant	44,3 mg/kg	Not relevant	
EC: 216-374-5	Inhalation	Not relevant	Not relevant	127 mg/m ³	Not relevant	
Butanone	Oral	Not relevant	Not relevant	31 mg/kg	Not relevant	
CAS: 78-93-3	Dermal	Not relevant	Not relevant	412 mg/kg	Not relevant	
EC: 201-159-0	Inhalation	Not relevant	Not relevant	106 mg/m ³	Not relevant	
propan-2-ol	Oral	51 mg/kg	Not relevant	26 mg/kg	Not relevant	
CAS: 67-63-0	Dermal	Not relevant	Not relevant	319 mg/kg	Not relevant	
EC: 200-661-7	Inhalation	178 mg/m ³	Not relevant	114 mg/m ³	Not relevant	

PNEC:

Identification				
ethanol	STP	580 mg/L	Fresh water	0,96 mg/L
CAS: 64-17-5	Soil	0,63 mg/kg	Marine water	0,79 mg/L
EC: 200-578-6	Intermittent	2,75 mg/L	Sediment (Fresh water)	3,6 mg/kg
	Oral	0,38 g/kg	Sediment (Marine water)	2,9 mg/kg
1-ethoxypropan-2-ol	STP	1250 mg/L	Fresh water	10 mg/L
CAS: 1569-02-4	Soil	1,97 mg/kg	Marine water	1 mg/L
EC: 216-374-5	Intermittent	19 mg/L	Sediment (Fresh water)	37,6 mg/kg
	Oral	0,142 g/kg	Sediment (Marine water)	3,76 mg/kg
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer 's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2007 EN 1149-2:1998 EN 1149-3:2004 UNE-EN ISO 18526-1 al 4:2020 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2022	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	-# (b) +	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Odour:

Alcohol

Odour threshold:

Not available

Alcohol

Not relevant *

Volatility:

Boiling point at atmospheric pressure: 78 - 133 °C

Vapour pressure at 20 °C: Not relevant *

Vapour pressure at 50 °C: Not relevant *

Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: 830,5 kg/m³

Relative density at 20 °C: 0,83

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 23/10/2024 Version: 1 Page 6/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration: Not relevant *

pH: 6 - 8

Vapour density at 20 °C:

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Not relevant *

Solubility properties:

Not relevant *

Decomposition temperature:

Melting point/freezing point:

Not relevant *

Not relevant *

Flammability:

Flash Point: 20 °C

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Not available

Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant *

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Exothermic reaction with: fluorine, chlorosulfonic acid, Strong oxidizing agents, fuming sulfuric acid. Risk of explosion with: lithium aluminium hydride, Alkali metals, hydrides, Alkaline earth metals. Violent reactions possible with: strong acids and strong bases.

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

Date of compilation: 23/10/2024 Version: 1 Page 7/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 10: STABILITY AND REACTIVITY (continued)

Other information:

Various plastics.

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: ethanol (1); propan-2-ol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acut	te toxicity	Genus
1-ethoxypropan-2-ol	LD50 oral	4400 mg/kg	Rat
CAS: 1569-02-4	LD50 dermal	8100 mg/kg	Rabbit
EC: 216-374-5	LC50 inhalation		
ethanol	LD50 oral	6200 mg/kg	Rat
CAS: 64-17-5	LD50 dermal	20000 mg/kg	Rabbit
EC: 200-578-6	LC50 inhalation	124,7 mg/L (4 h)	Rat
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat
propan-2-ol	LD50 oral	5280 mg/kg	Rat
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Product-specific aquatic toxicity:

Acute toxicity		Species	Genus
LC50	6775,1 mg/L (96 h)	Non-applicable	Fish
EC50	11764,85 mg/L (48 h)	Non-applicable	Crustacean

Substance-specific aquatic toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
ethanol	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
CAS: 64-17-5	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-578-6	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
1-ethoxypropan-2-ol	LC50	4600 mg/L (96 h)	Leuciscus idus	Fish
CAS: 1569-02-4	EC50	21100 mg/L (48 h)	Daphnia magna	Crustacean
EC: 216-374-5	EC50	Not relevant		
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
ethanol	NOEC	250 mg/L	Danio rerio	Fish
CAS: 64-17-5 EC: 200-578-6	NOEC	2 mg/L	Ceriodaphnia dubia	Crustacean

Date of compilation: 23/10/2024 Version: 1 Page 9/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradab	ility
ethanol	BOD5	Not relevant	Concentration	100 mg/L
CAS: 64-17-5	COD	Not relevant	Period	14 days
EC: 200-578-6	BOD5/COD	Not relevant	% Biodegradable	89 %
1-ethoxypropan-2-ol	BOD5	2,15 g O2/g	Concentration	100 mg/L
CAS: 1569-02-4	COD	Not relevant	Period	28 days
EC: 216-374-5	BOD5/COD	Not relevant	% Biodegradable	78 %
Butanone	BOD5	2,03 g O2/g	Concentration	Not relevant
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %
propan-2-ol	BOD5	1,19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2,23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0,53	% Biodegradable	86 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identifi	Identification		
ethanol	E		3
CAS: 64-17-5		Pow Log	-0.31
EC: 200-578-6		Potential	Low
1-ethoxypropan-2-ol		BCF	1
CAS: 1569-02-4		Pow Log	1
EC: 216-374-5		Potential	Low
Butanone		BCF	3
CAS: 78-93-3			0.29
EC: 201-159-0		Potential	Low
propan-2-ol		BCF	3
AS: 67-63-0		Pow Log	0.05
EC: 200-661-7		Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
ethanol	Koc	1	Henry	4,61E-1 Pa·m³/mol
CAS: 64-17-5	Conclusion	Very High	Dry soil	Yes
EC: 200-578-6	Surface tension	2,339E-2 N/m (25 °C)	Moist soil	Yes
Butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
propan-2-ol	Koc	1.5	Henry	8,207E-1 Pa·m³/mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Date of compilation: 23/10/2024 Version: 1 Page 10/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

	Code	Description	Waste class (Regulation (EU) No 1357/2014)	
I	08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number or ID number: UN1987

14.2 UN proper shipping name: ALCOHOLS, N.O.S. (ethanol)

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: II
14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 274, 601

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Maritime transport in bulk according to IMO

instruments:

Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



14.1 UN number or ID number: UN1987

14.2 UN proper shipping name: ALCOHOLS, N.O.S. (ethanol)

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: II14.5 Marine pollutant: No

14.6 Special precautions for user

according to IMO

Special regulations: 274

EmS Codes: F-E, S-D

Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: Not relevant **14.7 Maritime transport in bulk** Not relevant

instruments: Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

Date of compilation: 23/10/2024 Version: 1 Page 11/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1987

14.2 UN proper shipping name: ALCOHOLS, N.O.S. (ethanol)

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user

Physico-Chemical properties: see section 9 **Maritime transport in bulk** Not relevant

14.7 Maritime transport in bulk according to IMO

instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: ethanol (64-17-5) PT: (1,2,4,6); propan-2-ol (67-63-0) PT: (1,2,4)
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section		Description		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS			5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness. H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Date of compilation: 23/10/2024 Version: 1 Page 12/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

C2 562 - FLEXOTHINNER PE 20

Date of compilation: 23/10/2024 Version: 1

SECTION 16: OTHER INFORMATION (continued)

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.